Reach over 30’ in the most congested jobsites and challenging overhead work areas

Micro 26®

AC Electric Drive

- Micro - Compact overall length for jobsite maneuverability, elevators and tight work areas
- 36” roll-out deck extension for maximum workspace
- AC electric drive for extended duty cycle with standard AGM batteries
- 550 lb. Maximum platform capacity
- Integrated Leak Containment System® (LCS) Patent #11,112,060
- Single outlet for power to the platform and battery charging eliminates confusion
- Also available in an all-electric NetZero model: Micro 26®AE

Standard features

Performance

- AC electric drive
- Fully proportional drive & lift controls

Safety

- Entrapment mitigation designed into controls
- Active pothole protection
- Emergency shut-off at platform and lower controls
- Non-skid metal deck construction
- Descent and all-motion alarms
- Flashing beacon
- Drive speed interlock
- Multi-axis tilt sensor
- Multiple disc brakes
- Scissor maintenance lock
- Automatic parking brake
- Self-closing, full height platform gate

Serviceability

- Leak Containment System® (LCS)
- Lubrication-free scissor bearings
- Battery charger
- Slide-out service trays
- Onboard Diagnostics - no analyzer tool required

Options & Accessories

- Upper control box guard
- 1,000 W inverter
- Tool tray
- Cold weather package
- Proactive Platform Safety System® (PPSS)
- Perimeter lighting
- Sheet material rack
- Pipe racks (3 in., 4 in.)
- Extended Warranty

	US	Metric
Reach Dynamics - Indoor		
Maximum Working Height*	31 ft.*	9.6 m*
Maximum Platform Height*	25 ft.*	7.6 m*
Maximum Drive Height	25 ft.	7.6 m
Reach Dynamics - Outdoor		
Maximum Working Height*	24 ft.*	7.5 m*
Maximum Platform Height*	18 ft.*	5.5 m*
Maximum Drive Height	18 ft.	5.5 m
Platform		
Total Lift Capacity	550 lbs.	250 kg
Maximum Capacity (Occupants)	2 (Indoors), 1 (Outdoors)	
Platform Length x Width (Extended)	103.5 in. x 29.1 in.	2.63 m x 0.74 m
Platform Length x Width (Retracted)	68 in. x 29.1 in.	1.73 m x 0.74 m
Roll-Out Deck Extension	35.5 in.	0.9 m
Capacity on Deck Extension	250 lbs.	113 kg
Wheelbase	55 in.	1.4 m
Platform Entry	Full-Height Swing Gate	
Lanyard Attachment Points	4	
Key Overall Dimensions		
Length Stowed (Ladder/No ladder)	74 in./68 in.	1.88 m/1.73 m
Overall Width	31.9 in	0.81 m
Overall Height - Rails Up	91.3 in.	2.32 m
Overall Height - Rails Folded	78.3 in.	1.99 m
Weight** (Approximate)	4,300 lbs.**	1,950 kg**
Drive Performance		
Type	Proportional	
Outside Turning Radius	66.9 in.	1.7 m
Gradeability	25% (14°)	
Ground Clearance - Lowered	3.5 in.	9 cm
Ground Clearance - Elevated	0.6 in.	1.5 cm
Maximum Drive Speed - Lowered	2.8 mph	4.5 km/h
Maximum Drive Speed - Elevated	0.5 mph	0.8 km/h
Lift/Lower Speed	30/25 seconds	
Tires, Non-Marking	13 in. x 5 in.	32 cm x 12.5 cm
System Details		
Power Source	(4) 6V AGM Batteries, 240 Ah	

*Metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft. to platform height.
**Weight may vary with certain options or configurations.

MEC Aerial Work Platforms
Tel: 559.710.2425
Toll free: 1.877.725.4515
1401 S. Madera Ave., Kerman, CA 93630 USA
Email: info@MECawp.com
www.MECawp.com

MEC®, Micro 26®, Leak Containment System®, and Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., Inc.

97024 DTD 0126

Important – MEC lifts must be on a hard level surface while elevated.

Warranty – MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6.17.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.