



## SCISSOR LIFT

SLIM ELECTRIC



# 2632SE

## Electric Slim Scissor Lift

- Direct Electric Drive for Extended Duty Cycles and Faster Drive Speeds
- Standard Integrated Sheet Material Tray Allows 110 lbs. (50 kg) to be Stored and Lifted Outside the Platform
- Compact Maneuverability from Front Wheel Drive and Steer with Zero Inside Turn Radius
- Fully Proportional Lift and Drive Controls
- Standard Swing Gate
- Easy Serviceability with Swing Out Battery and Power Module Trays
- Maintenance-Free Batteries



**Do More with Direct Electric Drive, Standard Sheet Material Tray and Single Doorway Access**

## Standard Features

### Work Area

Standard Integrated Sheet Material Tray Designed and Approved by the Manufacturer  
Roll-Out Deck Extension with Incremental Locking Positions  
Standard Swing Gate  
Lanyard Attachments (4)

### Performance

Direct Electric Drive  
Fully Proportional Drive and Lift Controls  
Up to 25% Gradeability

### Power

Maintenance-Free Batteries  
Battery Charge Indicator

### Serviceability

Lubrication-Free Scissor Bearings  
Easy Maintenance Access to Mechanical and Electrical Components in a Slide-Out Tray  
Logically Grouped Components and Numbered Wiring for Easy Reference

### Safety

Dedicated Compartment Protects Electrical and Hydraulic Components  
Emergency Shut-Off at Platform and Lower Controls  
Non-Skid Metal Deck Construction  
Descent Alarm  
Drive Speed Interlock  
Multi-Axis Tilt Sensor  
Scissor Maintenance Lock  
Multiple Disc Brakes

### Other Features

Removable Upper Controls  
Voltage-Compensating Fully Automatic Battery Charger  
Fold-Down Guardrails  
Hour Meter  
Machine Tie Downs  
Non-Marking Tires  
All Motion Alarm  
Fork Lift Pocket  
Flashing Beacon (Continuous)

## Optional Features

Leak Containment System® (LCS) *Patent Pending*  
Proactive Platform Safety System® (PPSS)  
900W Inverter  
Tool Tray  
Cold Weather Package  
Pipe Rack  
Second Year Extended Warranty



### MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA  
Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520  
Email: info@MECawp.com | www.MECawp.com

MEC®, Micro 26®, Leak Containment System® & Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., LLC. Leak Containment System® is Patent Pending. 97015 DTD 1020

2632SE	U.S.	Metric
<b>Heights</b>		
Working Height*	32 ft.	10 m
Platform Height (Indoors)	26 ft.	8 m
Platform Height (Outdoors)	20 Ft.	6.1 m
Stowed Height (Top Guardrail)	91 in.	2.3 m
Stowed Height (Rails Folded)	78 in.	2 m
Stowed Height (Platform Floor)	48 in.	1.2 m
Guardrail Height	43.5 in.	1.1 m
Toeboard Height	6 in.	15 cm
Ground Clearance (Stowed)	4 in.	10 cm
Ground Clearance (Elevated)	.7 in.	2 cm
<b>Dimensions</b>		
Length-Stowed (Overall)	97 in.	2.5 m
Length-Stowed (Ladder Removed)	89.5 in.	2.3 m
Chassis Width	32 in.	81 cm
Platform Length (Extended)	124.5 in.	3.2 m
Platform Length (Retracted)	89.5 in.	2.27 m
Roll-Out Deck Length	35 in.	90 cm
Platform Width (Outside Sheet Tray)	33 in.	84 cm
Wheelbase	74 in.	1.9 m
Total Lift Capacity (Including Tray)	500 lbs	227 kg
Personnel Capacity	2 (Indoors); 1 (Outdoors)	
Roll-Out Deck Capacity	250 lbs	113 kg
Sheet Tray Capacity	110 lbs	50 kg
<b>Speed</b>		
Raise/Lower Speed	42 s / 30 s	
Drive Speed (Stowed)	2.5 mph	4.0 km/h
Drive Speed (Elevated)	0.5 mph	0.8 km/h
<b>Performance</b>		
Gradeability	25%	
Turning Radius (Inside)	0 in.	0 m
Weight**	4,870 lbs.	2210 kg
Power Source	24v 220Ah Maintenance-Free Batteries	
Controls	Proportional Drive & Lift Controls	
Tires	15 x 5 in.	38 x 13 cm

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

\*\*Weight may vary with certain options or configurations.

**Important** - MEC scissor lifts must be on a hard level surface while elevated.

**Warranty** - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

**Meets or exceeds** the requirements of ANSI A92.20 and CSA B354.6.

**Specifications** subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: