



# **3369 RT/ERT** **4069 RT/ERT**

## **Construction Grade Diesel & Electric Rough Terrain Scissor Lifts**

- 39 ft. (12 m) or 46 ft. (14 m) Working Height
- Standard 4-Wheel Drive with Traction Control (Diesel Only)
- Oscillating Front Axle
- 40% Gradeability
- Fully Proportional Drive & Lift Controls
- Roll-Out Deck Extension with Incremental Lock Positions
- Standard Integrated Sheet Material Rack Designed and Approved by MEC



**Flexible Platform Load Options Including Patented Sheet Material Rack**

## Standard Features

### Work Area

Standard Integrated Sheet Material Rack  
 Roll Out Deck Extension with Incremental Locking Positions  
 Standard Swing Gate  
 110V Power to Platform

### Performance

Standard 4-Wheel Drive with Traction Control (Diesel Only)  
 40% Gradeability  
 Oscillating Axle  
 Fully Proportional Drive and Lift Controls

### Power

Diesel Models (RT): Kubota D1105 Tier 4 Final  
 Electric Models (ERT): 48V DC Battery 375 Ah Pack

### Serviceability

Swing Out Engine Tray (Diesel Only)  
 Lubrication-Free Scissor Bearings  
 Easy Maintenance Access to Mechanical and Electrical Components without Raising Platform  
 Logically Grouped Components and Numbered Wiring for Easy Reference  
 Diagnostic Readout

### Safety

Diesel Models (RT): Black Foam Filled Tires  
 Electric Models (ERT): Non-Marking Foam Filled Tires  
 Dedicated Compartments Protect Electrical and Hydraulic Components  
 Emergency Shut-Off at Platform and Lower Controls  
 Non-Skid Metal Deck Construction  
 All Motion Alarm  
 Drive Speed Interlock  
 Multi-Axis Tilt Sensor  
 Multiple Disk Brakes, Manual Brake Release  
 Scissor Maintenance Lock  
 Four Wheel Automatic Parking Brake  
 Lanyard Attachments

### Other Features

Industrial Grade, Solid State Battery Charger (DC Only)  
 Fold-Down Guardrails  
 Hour Meter  
 Battery Charge Indicator (DC Only)  
 Machine Tie Downs  
 Flashing Beacon (Continuous)  
 Automotive Horn  
 Removable Upper Controls

## Optional Features

Auto-Leveling Outriggers  
 Air Line to Platform  
 Platform Work Lights  
 Cold Start Package  
 Pipe Rack  
 Second Year Extended Warranty



### MEC Aerial Work Platforms

Tel: 559.842.1500 | Fax: 559.842.1520  
 Toll free: 1.877.MEC LIFT | 1.877.632.5438  
 1401 S. Madera Avenue, Kerman, CA 93630 | USA  
 Email: info@MECawp.com | www.MECawp.com

MEC® is a registered trademark of California Manufacturing & Engineering Co., LLC.

97022 DTD 1118

69 Series Class Products	3369RT	3369ERT	4069RT	4069ERT
	Diesel	Electric	Diesel	Electric
<b>Heights</b>	<b>U.S./Metric</b>		<b>U.S./Metric</b>	
Working Height*	39 ft./12 m		46 ft./14 m	
Platform Height	33 ft./10 m		40 ft./12.2 m	
Maximum Drive Height	33 ft./10 m		40 ft./12.2 m	
Stowed Height (Top Guardrail)	102 in./2.59 m		108 in./2.74 m	
Stowed Height (Rails Folded)	72 in./1.83 m		78 in./1.98 m	
Stowed Height (Platform Floor)	58 in./1.47 m		65 in./1.65 m	
Guardrail Height	43 in./1.09 cm			
Toeboard Height	6 in./15 cm			
Ground Clearance	10 in./25 cm			
<b>Dimensions</b>				
Length-Stowed (Overall)**	10 ft. 6 in./3.2 m			
Chassis Width	69 in./1.75 m			
Platform Length (Extended)	14 ft. 1 in./4.29 m			
Platform Length (Retracted)	9 ft. 5 in./2.87 m			
Roll-Out Deck Length	4 ft. 8 in./1.42 m			
Platform Width (Outside)	60 in./1.52 m			
Sheet Rack Width	4 in./10.16 cm			
Wheelbase	90 in./2.29 m			
Total Lift Capacity	1,000 lbs./454 kg		800 lbs./363 kg	
Personnel Capacity	4		3	
Roll-Out Deck Capacity	300 lbs./136 kg			
Sheet Rack Capacity	300 lbs./136 kg			
<b>Speed</b>				
Raise/Lower Speed	40/40 sec		45/46 sec	
Drive Speed (Stowed)	3.75 mph/6.02 km/h			
Drive Speed (Elevated)	.40 mph/.65km/h			
<b>Performance</b>				
Gradeability	40%			
Turning Radius (Inside)	7 ft./2.15 m			
Weight**	9,480 lbs./4300 kg ; 9,700 lbs./4400 kg ; 11,133 lbs./5050 kg ; 11,354 lbs./5150 kg			
Power Source - RT	Kubota D1105 Tier 4 Final			
Power Source - ERT	48V DC Battery 375 Ah Pack			
Controls	Proportional			
Tires	26 in x 12-16.5 in./58 cm x 30.5-42 cm			

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height. \*\*Weight or length may vary with certain options or configurations. When platform is elevated, all models must be on a firm, planar surface.

**Warranty** - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

**Meets or exceeds** the requirements of ANSI A92.6-2006 and CSA B354.2-01.

**Specifications** subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: