

Micro 19°

Electric Scissor Lift

- Compact Size Yet Still Provides a Generous Work Area
- Fits on Most Elevators with Shortest Overall Length and Low GVW (Gross Vehicle Weight)
- 24 in. (61 cm) Roll-Out Deck Extension with Incremental Lock Positions
- Direct Electric Drive for Extended Duty Cycle, Smooth Control and Fewer Leak Points
- 2-Person Platform with 500 lbs. (227 kg) Capacity
- Fully Proportional Lift and Drive Controls



Standard Features

Work Area

Roll-Out Deck Extension with Incremental Locking Positions Standard Swing Gate **Lanyard Attachments** 110v Power to Platform

Performance

Direct Electric Drive Fully Proportional Drive and Lift Controls Up To 25% Gradeability

24v 115Ah AGM DC Electric Power (Maintenance-Free Batteries) **Battery Charge Indicator** Single 110v Receptacle at Chassis for Common Plug Connection for Battery Charger and Power to Platform

Serviceability

Lubrication-Free Scissor Bearings Easy Maintenance Access to Mechanical and Electrical Components in a Slide-Out Tray Logically Grouped Components and Numbered Wiring for Easy Reference

Safety

Lift Control Orientation Designed to Mitigate Overhead Entrapment **Dedicated Compartments Protect Electrical and Hydraulic Components Emergency Shut-Off at Platform** and Lower Controls

Other Features

Removable Upper Controls Voltage-Compensating Fully **Automatic Battery Charger** Hour Meter Machine Tie Downs

Non-Skid Metal Deck Construction Descent Alarm **Drive Speed Interlock** Scissor Maintenance Lock Multi-Axis Tilt Sensor Multiple Disc Brakes **Automatic Parking Brake**

Non-Marking Tires All Motion Alarm Fork Lift Pockets Flashing Beacon (Continuous)

Optional Features

900W Inverter **Tool Tray** Pipe Rack Cold Weather Package

Pro Leak Containment System® (LCS) - Patent Pending



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520 Email: info@MECawp.com | www.MECawp.com

MEC®, Micro 19®, Proactive Platform Safety System® and Leak Containment System® are registered trademarks of California Manufacturing & Engineering Co., LLC. Leak Containment System® is Patent Pending. 94542 DTD 0121 Distributed by:

| roactive Platform Safety | Important - MEC scissor lifts must be on a |
|-------------------------------|---|
| System® (PPSS) | Warranty - MEC Aerial Work Platforms carr |
| oak Containment System® (LCS) | parts and a five (5) year warranty on defecti |

Controls

Tires

Second Year Extended Warranty

| Micro 19 | U.S. | Metric |
|--------------------------------|---------------------------------|------------|
| Heights | | |
| Indoor Working Height* | 24 ft.* | 7.6 m* |
| Outdoor Working Height* | 21 ft.* | 6.5 m* |
| Indoor Platform Height | 18 ft. | 5.6 m |
| Outdoor Platform Height | 13 ft. | 4 m |
| Stowed Height (Top Guardrail) | 79 in. | 201 cm |
| Stowed Height (Platform Floor) | 39 in. | 99 cm |
| Guardrail Height | 39 in. | 99 cm |
| Toeboard Height | 6 in. | 15 cm |
| Ground Clearance (Stowed) | 2.5 in. | 6.4 cm |
| Ground Clearance (Elevated) | 0.6 in. | 1.5 cm |
| Dimensions | | |
| Length-Stowed (Overall) | 60 in. | 152 cm |
| Length-Stowed (Ladder Removed) | 54 in. | 137 cm |
| Chassis Width | 32 in. | 81 cm |
| Platform Length (Extended) | 78 in. | 198 cm |
| Platform Length (Retracted) | 54 in. | 137 cm |
| Roll-Out Deck Length | 24 in. | 61 cm |
| Platform Width | 27.5 in. | 70 cm |
| Wheelbase | 45 in. | 114 cm |
| Total Lift Capacity | 500 lbs. | 227 kg |
| Personnel Capacity | 2 | 2 |
| Roll-Out Deck Capacity | 250 lbs. | 113 kg |
| Speed | | |
| Raise/Lower Speed | 26 s | 20 s |
| Drive Speed (Stowed) | 2.5 mph | 4.0 km/h |
| Drive Speed (Elevated) | 0.5 mph | 0.8 km/h |
| Performance | | |
| Gradeability | 25% | 25% |
| Turning Radius (inside) | 18 in. | 46 cm |
| Weight** | 2,860 lbs.** | 1,297 kg** |
| Power Source | 24 v DC, 115Ah AGM Battery Pack | |

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

Proportional Drive & Lift Controls

23 cm x 10 cm

9 in. x 4 in.

**Weight may vary with certain options or configurations.

hard level surface while elevated.

y a one (1) year warranty on defective component ive structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.