

45-J Diesel **Telescopic Boom**

**Full-Featured,
Rugged, Simple,
Reliable**

- 51 ft. (15.5 m) Working Height with Standard 6 ft. (1.8 m) Jib for 135° Jib Range of Motion
- Continuous 360° Turntable Rotation
- Lightweight at 13,650 lbs. (6,200 kg) with 500 lbs. (227 kg) Standard Platform Capacity
- Solid Rough Terrain Tires
- Standard 90 in. (2.3 m) Platform Includes 3-Sided Entry with Swing Gate
- Full-Time Hydrostatic 4WD with Oscillating Front Axle and 40% Gradeability



Lightest Weight for Trucking and Floor Loading

Standard Features

Work Area

90 in. (2.3 m) Work Platform
3-Sided Entry with Swing Gate
500 lb. (227 kg) Platform Capacity
180° Platform Rotation
135° Jib Range of Motion
Power to Platform

Performance

360° Continuous Turntable Rotation
4WD Closed Loop Positive Traction Drive System
40% Gradeability
Oscillating Axle
Self-Leveling Platform
Low Engine RPM Elevated Operation
Two-Speed Drive Motors
50 ft. (15 m) Working Height
Full Drive Height

Control System

Triple Joystick Interface
Fully Proportional Multi-Function Controls

Power

Kubota V1505 Tier 4 Final

Safety

Emergency Shut-Off on
Platform and Chassis
Auxiliary Power Unit
Multi-Axis Tilt Sensor
Tilt Alarm and Horn
Four Wheel SAHR Braking System
Automotive Horn
Engine Shut Down Protection

Other Features

Hour Meter
Machine Tie-Downs and
Lifting Lugs
Lanyard Attachments
Standard Solid RT Tires
On-Board Diagnostics

Optional Features

Flashing Beacon (Continuous)
Platform Control Box Cover
Platform Work Lights
All Motion Alarm
7.5 kW Welder Ready Generator
3.5 kW AC Generator
Glazier Package
Cold Start Package
CSA Compliant Options
Proactive Platform Safety System (PPSS)
Second Year Extended Warranty



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA
Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520
Email: info@MECawp.com | www.MECawp.com

MEC® is a registered trademark of California Manufacturing & Engineering Co., LLC. 97020 DTD 0919

45-J	U.S.	Metric
Heights		
Working Height*	51 ft.	15.5 m
Platform Height	45 ft.	13.7 m
Drive Height	45 ft.	13.7 m
Maximum Outreach	38 ft.	11.6 m
Turntable Swing	360° Continuous	
Jib Range of Motion	135°	
Platform Rotation	180° (90° each side)	
Platform Size & Capacity		
Total Lift Capacity	500 lbs.	227 kg
Personnel Capacity	2	
Platform Width	90 in.	2.3 m
Platform Depth	40 in.	1.0 m
Platform Entry	1 End Swing Gate, 2 Slide Bars	
Dimensions		
Length-Stowed (Overall)	28 ft.	8.5 m
Width	96 in.	2.4 m
Overall Height	95 in.	2.4 m
Tailswing	35 in.	89 cm
Weight** (Approximately)	13,650 lbs.	6200 kg
Working Conditions		
Drive	4 Wheel Drive	
Gradeability	40%	
Ground Clearance	12 in.	30 cm
Breakover Angle	22° (40%)	
Axle Oscillation	10° (± 5°)	
Tires	Solid Rough Terrain	
Power		
Power Source	Kubota V1505 Tier 4	
Fuel Capacity	20 gal.	76 L
Hydraulic Oil Capacity	40 gal.	151 L
Movement		
Turning Radius (Inside)	78 in.	1.9 m
Drive Speed	3.5 mph	5.6 kph
Boom Lift Speed	30 Seconds	
Boom Extend Speed	20 Seconds	
Jib Lift Speed	15 Seconds	

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

**Weight may vary with certain options or configurations.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.5-2006 and CSA B354.4-02 as applicable.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: