



SCISSOR LIFT

SLIM ELECTRIC



2632SE^{AC}

Electric Slim Scissor Lift

- AC Electric Drive for Extended Duty Cycles, Smoother Controls and Faster Drive Speeds
- Standard Integrated Sheet Material Tray Allows 110 lbs. (50 kg) to be Stored and Lifted Outside the Platform
- Compact Maneuverability from Front Wheel Drive and Steer with Zero Inside Turn Radius
- Fully Proportional Lift and Drive Controls
- Standard Swing Gate
- Easy Serviceability with Swing Out Battery and Power Module Trays
- Maintenance-Free Batteries



Do More with AC Electric Drive, Standard Sheet Material Tray and Single Doorway Access

Standard Features

Work Area

Standard Integrated Sheet Material Tray Designed and Approved by the Manufacturer ***Indoor Use Only - U.S. Patent # 8,678,135
Roll-Out Deck Extension with Incremental Locking Positions
Standard Swing Gate
Lanyard Attachments (4)

Performance

AC Electric Drive
Fully Proportional Drive and Lift Controls
Up to 25% Gradeability

Power

Maintenance-Free Batteries
Battery Charge Indicator

Serviceability

Lubrication-Free Scissor Bearings
Easy Maintenance Access to Mechanical and Electrical Components in a Slide-Out Tray
Logically Grouped Components and Numbered Wiring for Easy Reference

Safety

Dedicated Compartment Protects Electrical and Hydraulic Components
Emergency Shut-Off at Platform and Lower Controls
Non-Skid Metal Deck Construction
Descent Alarm
Drive Speed Interlock
Multi-Axis Tilt Sensor
Scissor Maintenance Lock
Multiple Disc Brakes

Other Features

Removable Upper Controls
Voltage-Compensating Fully Automatic Battery Charger
Fold-Down Guardrails
Hour Meter
Machine Tie Downs
Non-Marking Tires
All Motion Alarm
Fork Lift Pocket
Flashing Beacon (Continuous)

Optional Features

Leak Containment System® (LCS) Patent #11,112,060
Upper Control Box Supplementary Guard
900W Inverter
Tool Tray
Cold Weather Package
Pipe Rack
Second Year Extended Warranty



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA
Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520
Email: info@MECawp.com | www.MECawp.com

MEC®, Micro 26®, Leak Containment System® & Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., LLC. Leak Containment System® is Patent #11,112,060.

97015 DTD 0522

| 2632SE ^{AC} | U.S. | Metric |
|--------------------------------------|--------------------------------------|------------|
| Heights | | |
| Indoor Working Height* | 32.2 ft.* | 10 m* |
| Outdoor Working Height* | 26.2 ft.* | 8 m* |
| Indoor Platform Height | 26.2 ft. | 8 m |
| Outdoor Platform Height | 20 Ft. | 6 m |
| Stowed Height (Top Guardrail) | 91 in. | 2.3 m |
| Stowed Height (Rails Folded) | 78 in. | 2 m |
| Stowed Height (Platform Floor) | 48 in. | 1.2 m |
| Guardrail Height | 43.5 in. | 1.1 m |
| Toeboard Height | 6 in. | 15 cm |
| Ground Clearance (Stowed) | 4 in. | 10 cm |
| Ground Clearance (Elevated) | .7 in. | 2 cm |
| Dimensions | | |
| Length-Stowed (Overall) | 97 in. | 2.5 m |
| Length-Stowed (Ladder Removed) | 89.5 in. | 2.3 m |
| Chassis Width | 32 in. | 81 cm |
| Platform Length (Extended) | 124.5 in. | 3.2 m |
| Platform Length (Retracted) | 89.5 in. | 2.27 m |
| Roll-Out Deck Length | 35 in. | 90 cm |
| Platform Width (Outside Sheet Tray) | 33 in. | 84 cm |
| Wheelbase | 74 in. | 1.9 m |
| Total Lift Capacity (Including Tray) | 550 lbs | 250 kg |
| Personnel Capacity | 2 (Indoors); 1 (Outdoors) | |
| Roll-Out Deck Capacity | 250 lbs | 113 kg |
| Sheet Tray Capacity | 110 lbs | 50 kg |
| Speed | | |
| Raise/Lower Speed | 42 s / 30 s | |
| Drive Speed (Stowed) | 3 mph | 5 km/h |
| Drive Speed (Elevated) | 0.5 mph | 0.8 km/h |
| Performance | | |
| Gradeability | 25% | |
| Turning Radius (Inside) | 0 in. | 0 m |
| Weight** | 4,870 lbs. | 2210 kg |
| Power Source | 24v 220Ah Maintenance-Free Batteries | |
| Controls | Proportional Drive & Lift Controls | |
| Tires | 15 x 5 in. | 38 x 13 cm |

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

**Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6 - 2017.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: