



# 4046SE<sup>AC</sup>

## Electric Slab Scissor Lift

- Indoors: 38.7 ft. (11.8 m) Platform Height and 44.7 ft. (13.8 m) Working Height
- Outdoors: 30 ft. (9.2 m) Platform Height and 36 ft. (11.2 m) Working Height
- AC Electric Drive for Extended Duty Cycles, Smoother Control and Faster Drive Speeds
- Compact Maneuverability from Front Wheel Drive and Steer with Zero Inside Turn Radius
- Drives at Full Height Indoors
- Fully Proportional Lift and Drive Controls
- Standard Swing Gate
- Easy Serviceability with Swing Out Battery and Power Module Trays
- 2-Person Platform (Indoors)/ 1-Person Platform (Outdoors) with 700 lb. (317 kg) Capacity

**Work at 45 ft. (13.8 m)  
Indoors from a Compact Base**



## Standard Features

### Work Area

Roll-Out Deck Extension with Incremental Locking Positions  
 Standard Swing Gate  
 Lanyard Attachments (4)

### Performance

AC Electric Drive  
 Fully Proportional Drive and Lift Controls

### Power

24v 300Ah AGM Batteries  
 Battery Charge Indicator

### Serviceability

Lubrication-Free Scissor Bearings  
 Easy Maintenance Access to Mechanical and Electrical Components  
 in a Slide-Out Tray  
 Logically Grouped Components and Numbered Wiring for Easy Reference

### Safety

Dedicated Compartment Protects Electrical and Hydraulic Components  
 Emergency Shut-Off at Platform and Lower Controls  
 Non-Skid Metal Deck Construction  
 Descent Alarm  
 Drive Speed Interlock  
 Multi-Axis Tilt Sensor  
 Scissor Maintenance Lock  
 Multiple Disc Brakes

### Other Features

Removable Upper Controls  
 Voltage-Compensating Fully Automatic Battery Charger  
 Fold-Down Guardrails  
 Hour Meter  
 Machine Tie Downs  
 Non-Marking Tires  
 All Motion Alarm  
 Fork Lift Pockets

## Optional Features

900W Inverter  
 Tool Tray  
 Upper Control Box Supplementary Guard

Cold Weather Package  
 Leak Containment System® (LCS)  
*Patent #11,112,060*  
 Pipe Rack  
 Second Year Extended Warranty



### MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA  
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520  
 Email: info@MECawp.com | www.MECawp.com

MEC®, Proactive Platform Safety System®, and Leak Containment System® are registered trademarks of California Manufacturing & Engineering Co., LLC. Leak Containment System® is Patent #11,112,060

97017 DTD 0522

4046SE <sup>AC</sup>	U.S.	Metric
<b>Heights</b>		
Indoor Working Height*	44.7 ft.*	13.8 m*
Outdoor Working Height*	36 ft.*	11.2 m*
Indoor Platform Height	38.7 ft.	11.8 m
Outdoor Platform Height	30 ft.	9.2 m
Stowed Height (Top Guardrail)	102 in.	2.6 m
Stowed Height (Rails Folded)	79 in.	2.0 m
Stowed Height (Platform Floor)	58 in.	1.5 m
Guardrail Height	43.5 in.	1.1 m
Toeboard Height	6 in.	15 cm
Ground Clearance (Stowed)	4 in.	10 cm
Ground Clearance (Elevated)	.7 in.	2 cm
<b>Dimensions</b>		
Length-Stowed (Overall)	98 in.	2.5 m
Length-Stowed (Ladder Removed)	89.5 in.	2.3 m
Chassis Width	47 in.	1.2 m
Platform Length (Extended)	124.5 in.	3.2 m
Platform Length (Retracted)	89.5 in.	2.3 m
Roll-Out Deck Length	35 in.	90 cm
Platform Width	44 in.	1.1 m
Wheelbase	74 in.	1.9 m
Total Lift Capacity	700 lbs.	317 kg
Personnel Capacity	2 ( Indoors); 1 (Outdoors)	
Roll-Out Deck Capacity	250 lbs.	113 kg
<b>Speed</b>		
Raise/Lower Speed	84 s / 48 s	
Drive Speed (Stowed)	3 mph	5 km/h
Drive Speed (Elevated)	0.5 mph	0.8 km/h
<b>Performance</b>		
Gradeability	25%	
Turning Radius (Inside)	0 in.	0 m
Weight**	7,000 lbs.	3,180 kg
Power Source	24 v 300Ah AGM Batteries	
Controls	Proportional Drive & Lift Controls	
Tires	15 x 5 in.	38 x 13 cm

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

\*\*Weight may vary with certain options or configurations.

**Important** - MEC scissor lifts must be on a hard level surface while elevated.

**Warranty** - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

**Meets or exceeds** the requirements of ANSI A92.20 and CSA B354.6 - 2017.

**Specifications** subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: