



Micro 26[®] AC Electric Scissor Lift

- Compact Size Almost 2 ft. (60 cm) Shorter Than Other 26 ft. (7.6m) Lifts
- AC Electric Drive for Extended Duty Cycle, Smoother Control and Faster Drive Speed
- Spacious 2-Person Platform (Indoors)/ 1-Person Platform (Outdoors) with 550 lb. (250 kg) Capacity
- Fully Proportional Lift and Drive Controls
- 36 in. (90 cm) Roll-Out Deck Extension with Incremental Lock Positions

Work Over 30 Ft. High Indoors in Tight Work Areas
with Micro Footprint



Standard Features

Work Area

Roll Out Deck Extension with Incremental Locking Positions
 Standard Full Height Swing Gate
 Lanyard Attachments (2)

Performance

AC Electric Drive
 Fully Proportional Drive and Lift Controls
 Up To 25% Gradeability

Power

240Ah Maintenance-Free Batteries
 Battery Charge Indicator

Serviceability

Lubrication-Free Scissor Bearings
 Easy Maintenance Access to Mechanical and Electrical Components in
 Swing Out Trays
 Parking Brake Release Switch for Towing

Safety

Lift Control Orientation Designed to Mitigate Entrapment
 Dedicated Compartments Protect Electrical and Hydraulic Components
 Emergency Shut-Off at Platform and Lower Controls
 Non-Skid Metal Deck Construction
 Descent Alarm
 Drive Speed Interlock
 Multi-Axis Tilt Sensor
 Multiple Disk Brakes
 Scissor Maintenance Lock
 Automatic Parking Brakes
 Automatic Pothole Protection

Other Features

Removable Upper Controls
 Voltage-Compensating Fully Automatic Battery Charger
 Hour Meter
 Machine Tie Downs
 Non-Marking Tires
 All-Motion Alarm
 Fork Lift Pockets
 Flashing Beacon

Optional Features

Leak Containment System[®] (LCS) *Patent #11,112,060*
 Upper Control Box Supplementary Guard
 900W Inverter
 Tool Tray
 Cold Weather Package
 Pipe Rack
 Second Year Extended Warranty



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520
 Email: info@MECawp.com | www.MECawp.com

MEC[®], Micro 26[®], Leak Containment System[®] & Proactive Platform Safety System[®] are registered trademarks of California Manufacturing & Engineering Co., LLC.
 Leak Containment System[®] is Patent #11,112,060

97024 DTD 0522

Micro 26 ^{®AC}	U.S.	Metric
Heights		
Indoor Working Height*	31 ft.*	9.6 m*
Outdoor Working Height*	24 ft.*	7.5 m*
Indoor Platform Height	25 ft.	7.6 m
Outdoor Platform Height	18 ft.	5.5 m
Stowed Height (Top Guardrail)	90.3 in.	2.3 m
Stowed Height (Rails Folded)	78.75 in.	2 m
Stowed Height (Platform Floor)	47 in.	1.2 m
Guardrail Height	43.5 in	1.1 m
Toeboard Height	6 in.	0.15 m
Ground Clearance (Stowed)	3 in.	7.62 cm
Dimensions		
Length-Stowed (Overall)	74 in.	1.88 m
Length-Stowed (Ladder Removed)	68 in	1.73 m
Chassis Width	31.9 in	.81 m
Platform Length (Extended)	103.5 in.	2.63 m
Platform Length (Retracted)	68 in.	1.73 m
Roll-Out Deck Length	35.5 in.	.9 m
Platform Width (Outside)	29.1 in.	.74 m
Wheelbase	55 in.	1.4 m
Total Lift Capacity	550 lbs.	250 kg
Personnel Capacity	2 (Indoors); 1 (Outdoors)	
Roll-Out Deck Capacity	250 lbs.	113 kg
Speed		
Raise/Lower Speed	30/25 sec	
Drive Speed (Stowed)	3 mph	5 km/h
Drive Speed (Elevated)	.5 mph	.8 km/h
Performance		
Gradeability	25% 14 degrees	
Turning Radius (Inside)	6 in.	15 cm
Weight**	4190 lbs.	1900 kg
Power Source	240Ah Maintenance-Free Batteries	
Controls	Proportional	
Tires	12 in. x 5 in	30 cm x 12.5 cm

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.
 **Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6 - 2017.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: