



## 3232SE<sup>AC</sup>

### AC Electric Drive

- Drives at full height, no outriggers required
- 32" wide with front-wheel AC drive for jobsite maneuverability
- Fold-down guardrails, 78.5" stowed height passes through a standard single doorway
- 550 lbs. platform capacity supports up to 2 workers and material
- 3' roll-out deck extension rated at 250 lbs. capacity
- AC direct electric drive for extended duty cycles
- Integrated Leak Containment System<sup>®</sup> (LCS) Patent #11,112,060
- Single outlet for power to the platform and battery charging eliminates confusion

Industry's only drive-at-full height 32' slim electric scissor for congested worksites and warehouse applications



## Standard features

### Performance

- AC electric drive
- Fully proportional drive & lift controls

### Safety

- Entrapment mitigation designed into controls
- Active pothole protection
- Emergency shut-off at platform and lower controls
- Non-skid metal deck construction
- Descent and all-motion alarms
- Flashing beacon
- Drive speed interlock
- Multi-axis tilt sensor
- Multiple disc brakes
- Scissor maintenance lock
- Automatic parking brake
- Self-closing, full height platform gate

### Serviceability

- Leak Containment System® (LCS), Patent #11,112,060
- Lubrication-free scissor bearings
- Battery charger
- Slide-out service tray
- Onboard Diagnostics - no analyzer tool required
- Rear forklift pockets
- Hour meter
- Machine tie down points

## Options & Accessories

- Upper control box guard
- 1,000 W inverter
- Tool tray
- Cold weather package
- Proactive Platform Safety System® (PPSS)
- Perimeter lighting
- Sheet material rack
- Pipe racks (3 in., 4 in.)
- Extended Warranty

	US	Metric
Reach Dynamics - Indoor		
Maximum Working Height*	38ft.*	11.8 m*
Maximum Platform Height*	32 ft.*	9.8 m*
Maximum Drive Height	32 ft.	9.8 m
Reach Dynamics - Outdoor		
Maximum Working Height*	30 ft.*	9.3 m*
Maximum Platform Height*	24 ft.*	7.3 m*
Maximum Drive Height	24 ft.	7.3 m
Platform		
Total Lift Capacity	550 lbs.	250 kg
Maximum Capacity (Occupants)	2 (Indoors), 1 (Outdoors)	
Platform Length x Width (Extended)	133.1 in. x 31.8 in.	3.38 m x 0.8 m
Platform Length x Width (Retracted)	97.6 in. x 31.8 in.	2.48 m x 0.8 m
Roll-Out Deck Extension	36.5 in.	0.93 m
Capacity on Deck Extension	250 lbs.	113 kg
Wheelbase	73.6 in.	1.87 m
Platform Entry	Full-Height Swing Gate	
Lanyard Attachment Points	4	
Key Overall Dimensions		
Length Stowed (Ladder/No ladder)	97.5 in./88.8 in.	2.47 m/2.25 m
Width	32.7 in	0.83 m
Overall Height - Rails Up	98.8 in.	2.51 m
Overall Height - Rails Folded	78.5 in.	2.05 m
Weight** (Approximate)	7,145 lbs.**	3,240 kg**
Drive Performance		
Type	Proportional	
Inside Turning Radius	0 in.	0 m
Gradeability	25% (14°)	
Ground Clearance - Lowered	3.9 in.	10 cm
Ground Clearance - Elevated	0.7 in.	1.9 cm
Maximum Drive Speed - Lowered	3.1 mph	5.0 km/h
Maximum Drive Speed - Elevated	0.5 mph	0.8 km/h
Lift/Lower Speed	52/38 seconds	
Tires, Non-Marking	15 in. x 5 in.	38 cm x 13 cm
System Details		
Power Source	(4) 12V AGM Batteries, 240 Ah	

\*Metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft. to platform height.

\*\*Weight may vary with certain options or configurations.

**Important** – MEC lifts must be on a hard level surface while elevated.

**Warranty** – MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

**Meets or exceeds** the requirements of ANSI A92.20 and CSA B354.6.17.

**Specifications** subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

### MEC Aerial Work Platforms

Tel: 559.710.2425

Toll free: 1.877.725.4515

1401 S. Madera Ave., Kerman, CA 93630 USA

Email: info@MECawp.com

www.MECawp.com

MEC®, Leak Containment System®, and Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., Inc. Leak Containment System® is Patent #11,112,060.

97043 DTD 0126