



1330SE

Micro Scissor Lift

- 13 ft. (3.9 m) Platform Height Indoors and 19 ft. (5.9 m) Working Height Indoors
- Fits on Most Elevators with Shortest Overall Length and Low GVW (Gross Vehicle Weight)
- 24 in. (61 cm) Roll-Out Deck Extension with Incremental Lock Positions
- Direct Electric Drive for Exceptional Duty Cycle, Smooth Control and Fewer Leak Points
- 2-Person Platform (Indoors)/ 1-Person Platform (Outdoors) with 500 lb. (227 kg) Capacity
- Fully Proportional Lift and Drive Controls
- Ultra Compact Design Fits Into Small and Tight Work Areas
- Compact Size Yet Still Provides a Generous Work Area

Lightweight, Micro Slim Scissor with True Slide-Out Deck



Standard Features

Work Area

Roll-Out Deck Extension with Incremental Locking Positions
 Standard Swing Gate
 Lanyard Attachments
 110v Power to Platform

Performance

Direct Electric Drive
 Fully Proportional Drive and Lift Controls
 Up to 25% Gradeability

Power

24v DC, 85Ah AGM Battery Pack (Maintenance-Free)
 Battery Charge Indicator
 Single 110v Receptacle at Chassis for Common Plug Connection for Battery Charger and Power to Platform

Serviceability

Lubrication-Free Scissor Bearings
 Easy Maintenance Access to Mechanical and Electrical Components
 Logically Grouped Components and Numbered Wiring for Easy Reference

Safety

| | |
|--|--------------------------|
| Lift Control Orientation Designed to Mitigate Overhead Entrapment | Descent Alarm |
| Dedicated Compartments Protect Electrical and Hydraulic Components | Drive Speed Interlock |
| Emergency Shut-Off at Platform and Lower Controls | Scissor Maintenance Lock |
| Non-Skid Metal Deck Construction | Multi-Axis Tilt Sensor |
| | Multiple Disc Brakes |
| | Automatic Parking Brake |

Other Features

| | |
|--|--------------------------------|
| Removable Upper Controls | Non-Marking Tires |
| Voltage-Compensating Fully Automatic Battery Charger | All Motion Alarm |
| Hour Meter | Fork Lift Pockets |
| Machine Tie Downs | Flashing Beacon (Continuous) |
| | Leak Containment System® (LCS) |

Optional Features

| | |
|----------------------|--|
| 900W Inverter | Upper Control Box |
| Tool Tray | Supplementary Guard |
| Pipe Rack | Proactive Platform Safety System® (PPSS) |
| Cold Weather Package | Second Year Extended Warranty |
| Anti-Fatigue Mat | |



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520
 Email: info@MECawp.com | www.MECawp.com

MEC®, Proactive Platform Safety System® and Leak Containment System® are registered trademarks of California Manufacturing & Engineering Co., LLC.
 Leak Containment System® is Patent #11,112,060

97010 DTD 0224

1330SE

| | U.S. | Metric |
|--------------------------------|------------------------------------|----------|
| Heights | | |
| Indoor Working Height* | 19 ft.* | 5.9m* |
| Outdoor Working Height* | 16 ft.* | 5 m* |
| Indoor Platform Height | 13 ft. | 3.9 m |
| Outdoor Platform Height | 10 ft. | 3 m |
| Stowed Height (Top Guardrail) | 80 in. | 203 cm |
| Stowed Height (Platform Floor) | 35 in. | 89 cm |
| Guardrail Height | 39 in. | 99 cm |
| Toeboard Height | 6 in. | 15 cm |
| Ground Clearance (Stowed) | 2.5 in. | 6 cm |
| Ground Clearance (Elevated) | 0.6 in. | 1.5 cm |
| Dimensions | | |
| Length-Stowed (Overall) | 57 in. | 145 cm |
| Length-Stowed (Ladder Removed) | 51 in. | 130 cm |
| Chassis Width | 31.5 in. | 80 cm |
| Platform Length (Extended) | 75 in. | 191 cm |
| Platform Length (Retracted) | 51 in. | 130 cm |
| Roll-Out Deck Length | 24 in. | 61 cm |
| Platform Width | 27.5 in. | 70 cm |
| Wheelbase | 41 in. | 104 cm |
| Total Lift Capacity | 530 lbs. | 240 kg |
| Personnel Capacity | 2 (Indoors); 1 (Outdoors) | |
| Roll-Out Deck Capacity | 250 lbs. | 113 kg |
| Speed | | |
| Raise/Lower Speed | 20 s | 20 s |
| Drive Speed (Stowed) | 2.5 mph | 4.0 km/h |
| Drive Speed (Elevated) | 0.5 mph | 0.8 km/h |
| Performance | | |
| Gradeability | 25% | 25% |
| Turning Radius (inside) | 18 in. | 46 cm |
| Weight** | 2,050 lbs.** | 930 kg** |
| Power Source | 24v DC, 85Ah AGM Battery Pack | |
| Controls | Proportional Drive & Lift Controls | |
| Tires | 9 in. | 23 cm |

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.
 **Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: