



# **3232SE**<sup>AC</sup> Electric Slim Scissor Lift

- Drives at Full Height Indoors Saving Time and Battery Energy Between Overhead Tasks
- Greater Productivity and Lower Cost of Ownership with Outrigger-Free Design
- AC Electric Drive for Extended Duty Cycles, Smoother Controls and Faster Drive Speeds
- Compact Maneuverability from Front Wheel Drive and Steer with Zero Inside Turn Radius
- Fully Proportional Lift and Drive
  Controls
- Standard Swing Gate
- Easy Serviceability with Swing Out Battery and Power Module Trays
- Maintenance-Free AGM Batteries



## **Standard Features**

#### Work Area

Roll-Out Deck Extension with Incremental Locking Positions Standard Swing Gate Lanyard Attachments (4)

### **Performance**

Drive at Full Height Indoors No Outriggers AC Electric Drive Fully Proportional Drive and Lift Controls Up to 25% Gradeability

#### Power

Maintenance-Free AGM Batteries Battery Charge Indicator

#### **Serviceability**

Lubrication-Free Scissor Bearings Easy Maintenance Access to Mechanical and Electrical Components in a Slide-Out Tray Logically Grouped Components and Numbered Wiring for Easy Reference

#### Safety

Dedicated Compartment Protects Electrical and Hydraulic Components Emergency Shut-Off at Platform and Lower Controls Non-Skid Metal Deck Construction Descent Alarm Drive Speed Interlock Multi-Axis Tilt Sensor Scissor Maintenance Lock Multiple Disc Brakes

#### **Other Features**

Leak Containment System® (LCS) Removable Upper Controls Voltage-Compensating Fully Automatic Battery Charger Fold-Down Guardrails Hour Meter Machine Tie Downs Non-Marking Tires All Motion Alarm Fork Lift Pocket Flashing Beacon (Continuous)

## **Optional Features**

900W Inverter Tool Tray Cold Weather Package Proactive Platform Safety System® (PPSS) Upper Control Box Supplementary Guard Pipe Rack Second Year Extended Warranty



#### **MEC Aerial Work Platforms**

**Tel: 559.842.1500** | 1401 S. Madera Avenue, Kerman, CA 93630 | USA Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520 Email: info@MECawp.com | www.MECawp.com

MEC®, Leak Containment System® & Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., LLC. Leak Containment System® is Patent #11,112,060. 97043 DTD 0224

<b>3232SE</b> <sup>ac</sup>	U.S.	Metric
Heights		
Indoor Working Height*	38 ft.*	11.6 m*
Outdoor Working Height*	30 ft.*	9.1 m*
Indoor Platform Height	32 ft.	9.8 m
Outdoor Platform Height	24 ft.	7.3 m
Stowed Height (Top Guardrail)	96 in.	2.4 m
Stowed Height (Rails Folded)	78 in.	2 m
Stowed Height (Platform Floor)	53 in.	1.3 m
Guardrail Height	43.5 in.	1.1 m
Toeboard Height	6 in.	15 cm
Ground Clearance (Stowed)	4 in.	10 cm
Ground Clearance (Elevated)	0.7 in.	1.8 cm
Dimensions		
Length-Stowed (Overall)	97 in.	2.5 m
Length-Stowed (Ladder Removed)	89.5 in.	2.3 m
Chassis Width	32 in.	81 cm
Platform Length (Extended)	124.5 in.	3.2 m
Platform Length (Retracted)	89.5 in.	2.3 m
Roll-Out Deck Length	35 in.	90 cm
Platform Width	29 in.	74 cm
Wheelbase	74 in.	1.9 m
Total Lift Capacity	550 lbs	250 kg
Personnel Capacity	2 (Indoors); 1 (Outdoors)	
Roll-Out Deck Capacity	250 lbs	113 kg
Speed		
Raise/Lower Speed	52 s / 38 s	
Drive Speed (Stowed)	3 mph	5 km/h
Drive Speed (Elevated)	0.5 mph	0.8 km/h
Performance		
Gradeability	25%	
Turning Radius (Inside)	0 in.	0 m
Weight**	7,145 lbs.	3240 kg
Power Source	24v 240Ah Maintenance-Free Batteries	
Controls	<b>Proportional Drive &amp; Lift Controls</b>	
Tires	15 x 5 in.	38 x 13 cm
*Metric equivalent of working beight adds 2m to platform beight 11.S. adds 6 ft. to platform beight		

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height. \*\*Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

**Meets or exceeds** the requirements of ANSI A92.20 and CSA B354.6 - 2017.

**Specifications** subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: