



85-J

Diesel Boom

- Dual Boom Mode Selection
Telescopic or Articulated
- Two Machines in One
- 2-Wheel Steer/4-Wheel Steer/
Crab Steer Standard
- Dual Capacity
600 lbs. (272 kg) Unrestricted,
900 lbs. (408 kg) Restricted
- 91 ft. (27.7 m) Working Height
with Standard 6 ft. (1.9 m) Jib for
135° Jib Range of Motion
- Axle-Based 4WD Traction Control
Drive
- Standard 90 in. (2.3 m) Platform
Includes 3-Sided Entry with Swing
Gate
- Ergonomic Platform Controls with
Proactive Platform Safety System®
Option
- Solid Rough Terrain Tires
- Deutz Turbo-Charged Engine Tier 4
- Optional Frame Leveling to Work
On Slopes



®

2 Machines in One - Telescopic & Articulated Boom Modes

Standard Features

Work Area

- 90 in. (2.3 m) Work Platform
- 3-Sided Entry with Swing Gate
- 600 lb. (272 kg) Unrestricted/900 lb. (408 kg) Restricted Platform Capacity
- 180° Platform Rotation
- 135° Jib Range of Motion
- Power to Platform
- 2-Wheel Steer/4-Wheel Steer/Crab Steer

Performance

- Telescopic & Articulated Patent Pending Dual Boom Mode Selection
- 360° Continuous Turntable Rotation
- 4WD Axle-Based Positive Traction Drive System
- 45% Gradeability
- Oscillating Axle
- Self-Leveling Platform
- Two-Speed Drive
- 91 ft. (28 m) Working Height
- Full Height Drive

Control System

- Triple Joystick Interface
- Fully Proportional Multi-Function Controls

Power

- 74 hp Deutz Tier 4 Final Diesel

Safety

- Emergency Shut-Off on Platform and Chassis
- Auxiliary Power Unit
- Multi-Axis Tilt Sensor
- Tilt Alarm and Horn
- All Motion Alarm
- Four Wheel SAHR Braking System
- Automotive Horn
- Engine Shut Down Protection

Other Features

- Hour Meter
- Machine Tie-Downs and Lifting Lugs
- Lanyard Attachments
- Standard Solid Rough Terrain Tires
- On-Board Diagnostics
- Flashing Beacon (Continuous)

Optional Features

- Frame Leveling to Work on Slopes - 7° Level Ability
- Platform Control Box Cover
- 7.5 kW Welder Ready Generator
- 12 kW Welder Ready Generator
- Platform Work Lights
- Glazier Package
- Cold Start Package
- Proactive Platform Safety System® (PPSS)
- Second Year Extended Warranty



MEC Aerial Work Platforms

Tel: 559.842.1500 | Fax: 559.842.1520
 Toll free: 1.877.MEC.LIFT | 1.877.632.5438
 1401 S. Madera Avenue, Kerman, CA 93630 | USA
 Email: info@MECawp.com | www.MECawp.com

MEC® and Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., LLC. *MEC Telescopic/Articulated Switchable-Mode Boom is Patent Pending. 97033 DTD 1023

85-J	US	Metric
Heights		
Working Height*	91 ft.*	27.7 m*
Platform Height	85 ft.	26 m
Drive Height	85 ft.	26 m
Turntable Swing	360° Continuous	
Jib Range of Motion	135°	
Platform Rotation	180° (90° each side)	
Up-and-Over Height	21 ft.	6.4 m
85-J Maximum Outreach		
Max. Telescopic Outreach (Unrestricted)	70 ft. @ 600 lbs.	21.3 m @ 272 kg
Max. Telescopic Outreach (Restricted)	64 ft. @ 900 lbs.	19.5 m @ 408 kg
Max. Articulated Outreach (Unrestricted)	56 ft. @ 600 lbs.	17.1 m @ 272 kg
Max. Articulated Outreach (Restricted)	50 ft. @ 900 lbs.	15.3 m @ 408 kg
Platform Size & Capacity		
Total Lift Capacity - Unrestricted	600 lbs.	272 kg
Total Lift Capacity - Restricted	900 lbs.	408 kg
Personnel Capacity	2	
Platform Width	90 in.	2.3 m
Platform Depth	40 in.	1.0 m
Platform Entry	1 End Swing Gate, 2 Slide Bars	
Dimensions		
Length-Stowed (Overall)	39 ft.	11.8 m
Width	102 in.	2.6 m
Overall Height	100 in.	2.5 m
Tailswing	5 ft. 5 in.	1.7 m
Weight** (Approximately)	37,500 lbs.**	17,009 kg**
Working Conditions		
Drive	Axle-Based 4 Wheel Drive	
Gradeability	45%	
Ground Clearance	14 in.	36 cm
Breakover Angle	22°	
Axle Oscillation	14° (±7°)	
Tires	Solid Rough Terrain	
Power		
Power Source	74 HP Deutz Tier 4 Final	
Fuel Capacity	40 gal.	151 L
Hydraulic Oil Capacity	48 gal.	182 L
Movement		
Turning Radius (Inside)	86 in.	2.2 m
Drive Speed	4 mph	6.4 kph
Boom Lift Speed	55 Seconds	
Boom Extend Speed	50 Seconds	
Jib Lift Speed	20 Seconds	

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.
 **Weight may vary with certain options or configurations.

Important - MEC lifts must be on a hard level surface while elevated. **Warranty** - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6.17.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: