



Micro 26[®]-XD^{AC} **Electric Scissor Lift** **with Xtra-Deck[®]**

Patent Pending

- Pull-Down Xtra-Deck[®] Allows Access Through Ceiling Panels Providing a Safe Solution to Gaining Additional Height into Confined Spaces
- Compact Size Almost 2 ft. (60 cm) Shorter Than Other 26 ft. (7.6m) Lifts
- AC Electric Drive for Extended Duty Cycle, Smoother Control and Faster Drive Speed
- Spacious 2-Person Platform (Indoors)/ 1-Person Platform (Outdoors) with 550 lb. (250 kg) Capacity
- Fully Proportional Lift and Drive Controls
- 36 in. (90 cm) Roll-Out Deck Extension with Incremental Lock Positions

**Work Over 30 Ft. High Indoors in Tight Work Areas
with Micro Footprint and Integral Xtra-Deck[®] Feature**



Standard Features

Work Area

Roll Out Deck Extension with Incremental Locking Positions
 Standard Full Height Swing Gate
 Lanyard Attachments (2)
 Xtra-Deck® Additional 16 in. (.4 m) Height Platform *Patent Pending*

Performance

AC Electric Drive
 Fully Proportional Drive and Lift Controls
 Up To 25% Gradeability

Power

240Ah Maintenance-Free AGM Batteries
 Battery Charge Indicator

Serviceability

Lubrication-Free Scissor Bearings
 Easy Maintenance Access to Mechanical and Electrical Components in
 Swing Out Trays
 Parking Brake Release Switch for Towing

Safety

Lift Control Orientation Designed to Mitigate Entrapment
 Dedicated Compartments Protect Electrical and Hydraulic Components
 Emergency Shut-Off at Platform and Lower Controls
 Non-Skid Metal Deck Construction
 Xtra-Deck® Solution to Standing on
 the Midrails Hazard
 Descent Alarm
 Drive Speed Interlock
 Multi-Axis Tilt Sensor

Multiple Disk Brakes
 Scissor Maintenance Lock
 Automatic Parking Brakes
 Automatic Pothole Protection

Other Features

Removable Upper Controls
 Voltage-Compensating Fully
 Automatic Battery Charger
 Hour Meter
 Machine Tie Downs

Non-Marking Tires
 All-Motion Alarm
 Fork Lift Pockets
 Flashing Beacon
 Leak Containment System® (LCS)

Optional Features

Upper Control Box Supplementary
 Guard
 900W Inverter
 Tool Tray

Cold Weather Package
 Pipe Rack
 Proactive Platform Safety
 System® (PPSS)
 Second Year Extended Warranty



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520
 Email: info@MECawp.com | www.MECawp.com

MEC®, Micro 26®, Leak Containment System® & Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., LLC.
 Leak Containment System® is Patent #11,112,060

97045 DTD 0424

| Micro 26®-XD ^{AC} | U.S. | Metric |
|--------------------------------|--------------------------------------|-----------------|
| Heights | | |
| Indoor Working Height* | 31 ft.* | 9.6 m* |
| Outdoor Working Height* | 24 ft.* | 7.5 m* |
| Indoor Platform Height | 25 ft. | 7.6 m |
| Outdoor Platform Height | 18 ft. | 5.5 m |
| Stowed Height (Top Guardrail) | 90.3 in. | 2.3 m |
| Stowed Height (Rails Folded) | 78.75 in. | 2 m |
| Stowed Height (Platform Floor) | 47 in. | 1.2 m |
| Guardrail Height | 43.5 in | 1.1 m |
| Toeboard Height | 6 in. | 0.15 m |
| Ground Clearance (Stowed) | 3 in. | 7.62 cm |
| Dimensions | | |
| Length-Stowed (Overall) | 74 in. | 1.88 m |
| Length-Stowed (Ladder Removed) | 68 in | 1.73 m |
| Chassis Width | 31.9 in | .81 m |
| Platform Length (Extended) | 103.5 in. | 2.63 m |
| Platform Length (Retracted) | 68 in. | 1.73 m |
| Roll-Out Deck Length | 35.5 in. | .9 m |
| Platform Width (Outside) | 29.1 in. | .74 m |
| Xtra-Deck® Width | 22 in. | 56 cm |
| Wheelbase | 55 in. | 1.4 m |
| Total Lift Capacity | 550 lbs. | 250 kg |
| Personnel Capacity | 2 (Indoors); 1 (Outdoors) | |
| Roll-Out Deck Capacity | 250 lbs. | 113 kg |
| Speed | | |
| Raise/Lower Speed | 30/25 sec | |
| Drive Speed (Stowed) | 3 mph | 5 km/h |
| Drive Speed (Elevated) | .5 mph | .8 km/h |
| Performance | | |
| Gradeability | 25% 14 degrees | |
| Turning Radius (Inside) | 6 in. | 15 cm |
| Weight** | 4,450 lbs. | 2020 kg |
| Power Source | 240Ah Maintenance-Free AGM Batteries | |
| Controls | Proportional | |
| Tires | 12 in. x 5 in | 30 cm x 12.5 cm |

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.
 **Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6 - 2017.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: