

mec

Reach over 30' in the most congested jobsites and challenging overhead work areas

## Micro 26®-XD

### with Xtra-Deck®

Patent #12,252,380

- Micro - Compact overall length for jobsite maneuverability, elevators and tight work areas
- 36" roll-out deck extension for maximum workspace
- AC electric drive for extended duty cycle
- 550 lb. Maximum platform capacity
- Single outlet for power to the platform and battery charging eliminates confusion
- Integrated Leak Containment System® (LCS) Patent #11,112,060

### Xtra-Deck®

- Platform within the platform to reach up 20" into tight overhead spaces
- Eliminates the need to stand on guardrails, and is OSHA compliant
- Integrated into the unit, stows out-of-the-way
- 250 lb. capacity on Xtra-Deck®. No reduction in platform capacity
- Rails provide a 22 in. x 20 in. work area



## Standard features

### Performance

- AC electric drive
- Fully proportional drive & lift controls
- Integrated Xtra-Deck®

### Safety

- Entrapment mitigation designed into controls
- Active pothole protection
- Emergency shut-off at platform and lower controls
- Non-skid metal deck construction
- Descent and all-motion alarms
- Flashing beacon
- Drive speed interlock
- Multi-axis tilt sensor
- Multiple disc brakes
- Scissor maintenance lock
- Automatic parking brake
- Self-closing, full height platform gate

### Serviceability

- Leak Containment System® (LCS)
- Lubrication-free scissor bearings
- Battery charger
- Slide-out service trays
- Onboard Diagnostics - no analyzer tool required

## Options & Accessories

- Upper control box guard
- 1,000 W inverter
- Tool tray
- Cold weather package
- Proactive Platform Safety System® (PPSS)

- Perimeter lighting
- Sheet material rack
- Pipe racks (3 in., 4 in.)
- Extended Warranty

## Xtra-Deck®



MEC's patented Xtra-Deck® can be deployed in less than 10 seconds.

As an integrated system, it stays with the machine when not in use and there is no reduction in capacity.

With four guardrails, no lanyard is required.

### MEC Aerial Work Platforms

Tel: 559.710.2425  
Toll free: 1.877.725.4515  
1401 S. Madera Ave., Kerman, CA 93630 USA  
Email: info@MECawp.com  
www.MECawp.com

MEC®, Xtra-Deck®, Micro 26®, Leak Containment System®, and Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., Inc. Xtra-Deck® is Patent #12,252,380, Leak Containment System® is Patent #11,112,060. 97045 DTD 0126

	US	Metric
<b>Reach Dynamics - Indoor</b>		
Maximum Working Height*	31 ft.*	9.6 m*
Maximum Platform Height*	25 ft.*	7.6 m*
Maximum Drive Height	25 ft.	7.6 m
<b>Reach Dynamics - Outdoor</b>		
Maximum Working Height*	22.4 ft.*	6.8 m*
Maximum Platform Height*	16.4 ft.*	4.8 m*
Maximum Drive Height	16.4 ft.	4.8 m
<b>Xtra-Deck® - Patented</b>		
Capacity on Xtra-Deck®	250 lb.	113 kg
Length x Width	17.5 in x 22 in.	44.5 cm x 56 cm
Additional Height	16 in.	40.6 cm
<b>Platform</b>		
Total Lift Capacity	550 lbs.	250 kg
Maximum Capacity (Occupants)	2 (Indoors), 1 (Outdoors)	
Platform Length x Width (Extended)	103.5 in. x 29.1 in.	2.63 m x 0.74 m
Platform Length x Width (Retracted)	68 in. x 29.1 in.	1.73 m x 0.74 m
Roll-Out Deck Extension	35.5 in.	0.9 m
Capacity on Deck Extension	250 lbs.	113 kg
Wheelbase	55 in.	1.4 m
Platform Entry	Full-Height Swing Gate	
Lanyard Attachment Points	4	
<b>Key Overall Dimensions</b>		
Length Stowed (Ladder/No ladder)	74 in./68 in.	1.88 m/1.73 m
Overall Width	31.9 in	0.81 m
Overall Height - Rails Up	90.3 in.	2.3 m
Overall Height - Rails Folded	78.75 in.	2 m
Weight** (Approximate)	4,450 lbs.**	2,020 kg**
<b>Drive Performance</b>		
Type	Proportional	
Outside Turning Radius	66.9 in.	1.7 m
Gradeability	25% (14°)	
Ground Clearance - Lowered	3.8 in.	9.7 cm
Ground Clearance - Elevated	0.6 in.	1.5 cm
Maximum Drive Speed - Lowered	3 mph	5 km/h
Maximum Drive Speed - Elevated	0.5 mph	0.8 km/h
Lift/Lower Speed	30/25 seconds	
Tires, Non-Marking	13 in. x 5 in.	32 cm x 12.5 cm
<b>System Details</b>		
Power Source	(4) 6V AGM Batteries, 240 Ah	

\*Metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft. to platform height.  
\*\*Weight may vary with certain options or configurations.

**Important** – MEC lifts must be on a hard level surface while elevated.

**Warranty** – MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

**Meets or exceeds** the requirements of ANSI A92.20 and CSA B354.6.17.

**Specifications** subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.