



3369 RT/ERT **4069 RT/ERT**

Construction Grade Diesel & Electric Rough Terrain Scissor Lifts

- 39 ft. (12 m) or 46 ft. (14 m) Working Height
- Standard 4-Wheel Drive with Traction Control (Diesel Only)
- Oscillating Front Axle
- 40% Gradeability
- Fully Proportional Drive & Lift Controls
- Roll-Out Deck Extension with Incremental Lock Positions
- Standard Integrated Sheet Material Rack Designed and Approved by MEC



Flexible Platform Load Options Including Sheet Material Rack

Standard Features

Work Area

Standard Integrated Sheet Material Rack
Roll Out Deck Extension with Incremental Locking Positions
Standard Swing Gate
110V Power to Platform

Performance

Standard 4-Wheel Drive with Traction Control (Diesel Only)
40% Gradeability
Oscillating Axle
Fully Proportional Drive and Lift Controls

Power

Diesel Models (RT): Kubota D1105 Tier 4 Final
Electric Models (ERT): 48V DC Battery 375 Ah Pack

Serviceability

Swing Out Engine Tray (Diesel Only)
Lubrication-Free Scissor Bearings
Easy Maintenance Access to Mechanical and Electrical Components without Raising Platform
Logically Grouped Components and Numbered Wiring for Easy Reference
Diagnostic Readout

Safety

Diesel Models (RT): Black Foam Filled Tires
Electric Models (ERT): Non-Marking Foam Filled Tires
Dedicated Compartments Protect Electrical and Hydraulic Components
Emergency Shut-Off at Platform and Lower Controls
Non-Skid Metal Deck Construction
All Motion Alarm
Drive Speed Interlock
Multi-Axis Tilt Sensor
Multiple Disk Brakes, Manual Brake Release
Scissor Maintenance Lock
Four Wheel Automatic Parking Brake
Lanyard Attachments

Other Features

Industrial Grade, Solid State Battery Charger (DC Only)
Fold-Down Guardrails
Hour Meter
Battery Charge Indicator (DC Only)
Machine Tie Downs
Flashing Beacon (Continuous)
Automotive Horn
Removable Upper Controls

Optional Features

Auto-Leveling Outriggers
Air Line to Platform
Platform Work Lights
Cold Start Package
Pipe Rack
Second Year Extended Warranty



MEC Aerial Work Platforms

Tel: 559.710.2425 | Toll free: 1.877.725.4515
1401 S. Madera Avenue, Kerman, CA 93630 | USA
Email: info@MECawp.com | www.MECawp.com

MEC® is a registered trademark of California Manufacturing & Engineering Co., LLC.
97022 DTD 0425

69 Series Class Products	3369RT	3369ERT	4069RT	4069ERT
	Diesel	Electric	Diesel	Electric
Heights	U.S./Metric		U.S./Metric	
Working Height*	39 ft./12 m		46 ft./14 m	
Platform Height	33 ft./10 m		40 ft./12.2 m	
Maximum Drive Height	33 ft./10 m		40 ft./12.2 m	
Stowed Height (Top Guardrail)	102 in./2.59 m		108 in./2.74 m	
Stowed Height (Rails Folded)	72 in./1.83 m		78 in./1.98 m	
Stowed Height (Platform Floor)	58 in./1.47 m		65 in./1.65 m	
Guardrail Height	43 in./1.09 cm			
Toeboard Height	6 in./15 cm			
Ground Clearance	10 in./25 cm			
Dimensions				
Length-Stowed (Overall)**	10 ft. 6 in./3.2 m			
Chassis Width	69 in./1.75 m			
Platform Length (Extended)	14 ft. 1 in./4.29 m			
Platform Length (Retracted)	9 ft. 5 in./2.87 m			
Roll-Out Deck Length	4 ft. 8 in./1.42 m			
Platform Width (Outside)	60 in./1.52 m			
Sheet Rack Width	4 in./10.16 cm			
Wheelbase	90 in./2.29 m			
Total Lift Capacity	1,000 lbs./454 kg		800 lbs./363 kg	
Personnel Capacity	2 Persons (Outdoors)			
Roll-Out Deck Capacity	300 lbs./136 kg			
Sheet Rack Capacity	300 lbs./136 kg			
Speed				
Raise/Lower Speed	40/40 sec		45/46 sec	
Drive Speed (Stowed)	3.75 mph/6.02 km/h			
Drive Speed (Elevated)	.40 mph/.65km/h			
Performance				
Gradeability	40%			
Turning Radius (Inside)	7 ft./2.15 m			
Weight**	9,480 lbs./4300 kg ; 9,700 lbs./4400 kg ; 11,133 lbs./5050 kg ; 11,354 lbs./5150 kg			
Power Source - RT	Kubota D1105 Tier 4 Final			
Power Source - ERT	48V DC Battery 375 Ah Pack			
Controls	Proportional			
Tires	26 in x 12-16.5 in./58 cm x 30.5-42 cm			

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height. **Weight or length may vary with certain options or configurations. When platform is elevated, all models must be on a firm, planar surface.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: