



Micro 26[®]-XD

with Patented Xtra-Deck[®]

Patent #12,252,380

- Micro - Compact overall length for jobsite maneuverability
- 36" roll-out deck extension for maximum workspace
- AC electric drive for extended duty cycle
- 550 lb. Maximum platform capacity
- Patented Leak Containment System[®] (LCS), Patent #11,112,060

Xtra-Deck[®]

- Platform within the platform to reach up 20" into tight overhead spaces
- Eliminates the need to stand on guardrails, and is OSHA compliant
- Integrated into the unit, stows out-of-the-way
- 250 lb. capacity on Xtra-Deck[®]. No reduction in platform capacity
- No lanyard required on Xtra-Deck, rails on all four sides

Reach over 30' in the most congested jobsites and challenging overhead work areas





Standard features

Performance

- AC electric drive
- Fully proportional drive & lift controls
- Integrated Xtra-Deck®

Safety

- Entrapment mitigation design designed into controls
- Active pothole protection
- Emergency shut-off at platform and lower controls
- Non-skid metal deck construction
- Descent & all-motion alarms
- Flashing beacon
- Drive speed interlock
- Multi-axis tilt sensor
- Multiple disc brakes
- Scissor maintenance lock
- Automatic parking brake

Serviceability

- Leak Containment System® (LCS)
- Lubrication-free scissor bearings
- Battery charger
- Slide-out service trays
- Onboard Diagnostics - no analysis required

Options & Accessories

- Upper control box guard
- 1,000 W inverter
- Tool tray
- Cold weather package
- Proactive Platform Safety System® (PPSS)
- Perimeter lighting
- Sheet material tray
- Pipe racks (3 in., 4 in.)
- Extended Warranty

Xtra-Deck®



MEC's patented Xtra-Deck® can be deployed in less than 10 seconds.

As an integrated system, it stays with the machine when not in use and there is no reduction in capacity.

With four guardrails, no lanyard is required.

MEC Aerial Work Platforms

Tel: 559.710.2425
Toll free: 1.877.725.4515
1401 S. Madera Ave., Kerman, CA 93630 USA
Email: info@MECawp.com
www.MECawp.com

MEC®, Xtra-Deck®, Micro 26®, Leak Containment System®, and Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., Inc. Xtra-Deck® is Patent #12,252,380, Leak Containment System® is Patent #11,112,060. 97045 DTD 0925

	US	Metric
Reach Dynamics - Indoor		
Maximum Working Height*	31 ft.*	9.6 m*
Maximum Platform Height*	25 ft.*	7.5 m*
Maximum Drive Height	25 ft.	7.5 m
Reach Dynamics - Outdoor		
Maximum Working Height*	24 ft.*	7.5 m*
Maximum Platform Height*	18 ft.*	5.5 m*
Maximum Drive Height	18 ft.	5.5 m
Xtra-Deck® - Patented		
Capacity on Xtra-Deck®	250 lb.	113 kg
Length x Width	17.5 in x 22 in.	44.5 cm x 56 cm
Additional Height	16 in.	40.6 cm
Platform		
Total Lift Capacity	550 lbs.	250 kg
Maximum Capacity (Occupants)	2 (Indoors), 1 (Outdoors)	
Platform Length x Width (Extended)	103.5 in. x 29.1 in.	2.63 m x .74 m
Platform Length x Width (Retracted)	68 in. x 29.1 in.	1.73 m x .74 m
Roll-Out Deck Extension	35.5 in.	.9 m
Capacity on Deck Extension	250 lbs.	113 kg
Wheelbase	55 in.	1.4 m
Platform Entry	Full-Height Swing Gate	
Lanyard Attachment Points	4	
Key Overall Dimensions		
Length Stowed (Ladder/No ladder)	74 in./68 in.	1.88 m/1.73 m
Overall Width	31.9 in	.81 m
Overall Height - Rails Up	90.3 in.	2.3 m
Overall Height - Rails Folded	78.75 in.	2 m
Weight** (Approximate)	4,450 lbs.**	2,020 kg**
Drive Performance		
Type	Proportional	
Outside Turning Radius	72 in.	182.9 cm
Gradeability	25% 14 degrees	
Ground Clearance - Lowered	3.8 in.	9.7 cm
Ground Clearance - Elevated	0.6 in.	1.6 cm
Maximum Drive Speed - Lowered	3 mph	5 km/h
Maximum Drive Speed - Elevated	.5 mph	.8 km/h
Lift/Lower Speed	30/25 seconds	
Tires, Non-Marking	12 in. x 5 in	30 cm x 12.5 cm
System Details		
Power Source	(4) 6V AGM Batteries, 240 Ah	

*Metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft. to platform height.

**Weight may vary with certain options or configurations.

Important – MEC lifts must be on a hard level surface while elevated.

Warranty – MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6.17.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.