



CD-9T Diesel Carry Deck Crane

Key Features:

- Low-profile engine mounted on the side of chassis for maximum visibility and maximum carry-deck area
- Hydrostatic transmission with 4WD standard
- Four steering modes: 4-wheel, Crab, 2-wheel front and 2-wheel rear standard
- Foam-filled, non-marking tires standard
- Large, spacious cab with full-pressure hydraulic controls
- Enclosed comfort cab with air conditioning and heat, and a suspension seat standard
- Load Management System and a 4-camera view on screen in the cab
- Swing-out rear counterweight for superior boom access for service
- Perimeter lighting standard




Preliminary Key Specifications

	On Rubber	Outriggers
Max Boom Height	46' - 8"	46' - 8"
Capacity (front)	4,450 lb	6,100 lb
Max Outreach	40' - 0"	40' - 0"
Capacity (front)	500 lb	1,400 lb
Max Lifting Capacity	11,400 lb	18,000 lb
Std. Boom Extension	10'	
Max Drive Speed	15 mph	
Power Source	Deutz 74hp Turbo Diesel	
Stowed Height	7' - 10"	
Overall Length	19' - 0"	
Overall Width	6' - 6"	9' - 10"
Tailswing	24"	
Wheelbase	8' - 1.5"	
Gradeability	25%	
Ground Clearance	10-3/8"	
Gross Vehicle Weight	19,800 lb	
Tires	Foam-filled, Non-Marking	

CD-9T Diesel Carry Deck Crane



Load Chart:



Capacity Chart:

CAPACITIES APPLY TO OPERATION ON FIRM LEVEL SURFACE					
LOAD RADIUS FEET	MAIN BOOM OR EXTENSION CAPACITIES IN POUNDS				
	360° ROTATION		OVER FRONT		
	ON RUBBER	ON OUTRIGGERS	ON RUBBER	ON OUTRIGGERS	
MAIN BOOM	5	9400	17000	11400	18000
	6	7000	14000	10000	14000
	8	5000	10000	8100	10000
	10	3750	7700	6100	7700
	12	2850	6100	4450	6100
	14	2250	5200	3400	5200
	16	2000	4300	2700	4400
	18	1650	3700	2200	3900
	20	1350	3200	1800	3400
	22	1150	2800	1550	3050
	24	1000	2450	1350	2800
	26	850	2100	1200	2550
	28	750	1900	1100	2350
	30	650	1700	1000	2150
10' BOOM EXT.	32	450	1600	900	1950
	34	350	1500	800	1800
	36	250	1400	700	1650
	38	200	1300	600	1500
	40	150	1150	500	1400
	10-FOOT BOOM EXTENSION - STRAIGHT OR OFFSET				
MAIN BOOM ANGLE					
BOOM EXTENSION ANGLE					
	0°	30°	45°	60°	70°
† 0°	2250	2600	3200	5000	7000
† 30°	--	2250	2500	3000	3300