

# PLUS (+) Series

## Micro 26<sup>®</sup> & Slab Electric Scissors

**NEW**

Micro 26<sup>®</sup>+ | Micro 26<sup>®</sup>-XD+ | 3232+ | 3346+  
4046+ | 4555+ | 1930+ & 2632+ (Canada Only)



### Higher Platform Capacities

50 to 100 lbs. greater lift capacities reduce overload nuisances. Plus 300 lbs capacity on all deck extensions and Xtra-Deck<sup>®</sup> (XD).

### 22% Greater Duty Cycles

High-efficiency PMSR AC drive motors recapture 30% of the lifting energy -- increasing duty by 22% for extended battery life.

### Lower Operating Costs

Durability improvements, including an advanced rubber compound so non-marking tires can withstand abuse, and a 4-in-1 motor controller that reduces system connections.

### Enhanced Operator Controls

Larger screen, thicker membrane switches, and proportional lowering for smoother, more precise control.

MODELS	MAX PLATFORM HEIGHT	CAPACITY (LB.) OVERALL / DECK	LENGTH STOWED	OVERALL WIDTH	MACHINE WEIGHT
Micro 26+	26 ft.	600 / 300	74 in.	32 in.	4,450 lb
Micro 26-XD+	26 ft.	600 / 300	74 in.	32 in.	4,450 lb
3232+	32 ft.	600 / 300	97 in.	32 ft. 7 in.	7,145 lb
3346+	33 ft.	900 / 300	97 in.	46 in.	6,000 lb
4046+	40 ft.	800 / 300	98 in.	46 in.	7,200 lb
4555+	45 ft.	800 / 300	112 in.	55 in.	7,760 lb
*1930+	19 ft. 4 in.	600 / 300	73 in.	30 in.	3,440 lb
*2632+	26 ft.	600 / 300	97 in.	32 in.	4,870 lb

\*Canada only

**Standard Features Include:** **NEW** Theft deterrent control box bracket, **NEW** Lockable battery disconnect, **NEW** Magnetic gate latch, Leak Containment System<sup>®</sup>, AGM Maintenance-Free Batteries



# PLUS (+) Series

## Micro 19<sup>®</sup> Scissor Lifts

**NEW**

Micro 19<sup>®</sup>+ | Micro 19<sup>®</sup>-XD+



### Greater Platform Capacity

Platform capacity increases by 100 lb, and deck extension and Xtra-Deck<sup>®</sup> capacity rises to 300 lb – both designed to reduce overload nuisances.

### More Productive Time Per Charge

Duty cycles increase by 8% due to the new AC front wheel drive brushless motors.

### Tighter Turning Radius

High angle steering coupled with the front-wheel drive motors make jobsite navigation easy.

### Easier Transport Loading and Jobsite Navigation

12" diameter, 4" wide wheels paired with front-wheel drive help power onto trailers and trucks while handling ramps, thresholds, and uneven jobsite surfaces.

### Durable, True Non-Marking Tires

Advanced rubber compound formula can withstand jobsite abuse from curbs, sharp objects and wear.

MODELS	MAX PLATFORM HEIGHT	CAPACITY (LB.) OVERALL / DECK	LENGTH STOWED	OVERALL WIDTH	MACHINE WEIGHT
Micro 19 <sup>®</sup> +	18 ft. 4 in.	600 / 300	60 in.	32 in.	2,995 lb
Micro 19 <sup>®</sup> -XD+	18 ft. 4 in.	600 / 300	60 in.	32 in.	3,065 lb



The MEC<sup>®</sup> Xtra-Deck<sup>®</sup> stands out from the rest – it deploys in less than 10 seconds and doesn't de-rate the platform capacity.

**Standard Features Include:** **NEW** Theft deterrent control box bracket, **NEW** Lockable battery disconnect, **NEW** Magnetic gate latch, Leak Containment System<sup>®</sup>, AGM Maintenance-Free Batteries

